

CONVERSIONS

The following is a step-by-step list of converting from L.P. Gas to Natural Gas or from natural Gas to L.P.

1. Remove the top panel in the back from the Grill to gain access to the regulator
2. Remove the existing regulator and install the appropriate regulator provided by LUXOR manufacturer, and corresponding with the gas type
3. Remove the Grill's cooking grids and burners. Be cautious and do not move or damage the electrodes on the igniter..
4. At the entrance of the burner throat find the main burner orifices. Unscrew these orifices and put them aside.
5. Replace EACH INDIVIDUAL ORIFICE WITH THE SPECIFIED ORIFICE provided by American Heating Technologies. (You must replace the main burner orifices, smoker burner orifice, back burner orifices, and side burner orifices.)
6. Refit the access panel in the back of the grill
7. Attach the main burners onto the burner valve orifices. Do not damage or move the igniter electrodes.
8. After correctly converting the Grill and testing for leaks, follow the instructions for lighting the grill and check the burner flames for possible irregularities (color, look, etc.)
9. Adjust the burner "Low" setting by using a long stemmed flat-head screwdriver, inserting the screwdriver into the Burner Control Valve stem, and turn the adjustment screw (turn counter clockwise) producing a stable flame when the Burner Control Valve is set on "low." This applies to all operations / burner types.
10. If the burner is running properly, place the cooking grids back in position.
11. To indicate the change made, make sure to mark the proper setting on the rating plate.)

WARNING

WHEN CONVERTING A UNIT GAS TYPE YOU MUST ONLY USE
A CONVERSION KIT SPECIFIED BY
AMERICAN HEATING TECHNOLOGIES.