

SAFETY PRACTICES & PRECAUTIONS

- 20) If the grill is installed by a professional installer or technician, be sure that they show you where your gas supply shut-off is located. All gas lines must have a shut-off that is readily and easily accessible. If you smell gas, check for gas leaks immediately. Check only with a soap and water solution.. NEVER CHECK FOR GAS LEAKS WITH AN OPEN FLAME.
- 21) Keep any electrical supply cord away from any heated surface. Electrical cords should be placed away from walkways to avoid tripping hazard.
- 22) Do not use this unit until a leak check has been performed.
- 23) Do not move grill while hot or in use.
- 24) Do not operate this unit under the influence of drugs, heavy medication, or alcohol.
- 25) Do not lean on shelves or place more than 25 pounds on a side shelf.
- 26) If any burner does not light or goes out during operation, turn off all gas control knobs with hood open and wait (5) minutes before attempting to re-light.

LEAK TESTING

NOTE: NEVER USE GRILL WITHOUT LEAK TESTING

HOW TO PERFORM A LEAK TEST:

- A) Create a soapy solution of half water and half dishwashing detergent.
- B) Make sure that all control knobs are in the off position.
- C) Turn on fuel supply. Turn cylinder valve knob counter clockwise (right to left) one rotation.
- D) Apply soap solution generously by paint brush or squirt bottle on all connections and fittings.
- E) If you see any “growing” bubbles on any of the connection points, you have detected a gas leak. IMMEDIATELY turn off the gas from the main gas source.
- F) A leak may be stopped by tightening the loose joint, or by replacing the faulty part with a replacement part recommended by the manufacturer.
- E) Do not attempt to repair the cylinder valve if it should become damaged, THE CYLINDER MUST BE REPLACED.
- E) Check the hose for signs of cracks abrasion and leaks.

DANGER: TO PREVENT EXPLOSION OR FIRE HAZARD:

DO NOT use or permit sources of ignition including smoking in the area while doing a leak test
Perform leak tests outdoors only. Never use flame or fire to do a leak test.